

Wired 2D Barcode Scanner

POS760H

Application Industry

Store / Restaurant / Pharmacy / Ticket barrier



Specifications

Material	ABS+PVC+PC	Interface	USB (RS232 can be customized)
Power Supply	DC 5V ±5%	Sensor	Planar CMOS sensor 640*480
Operating Current	168mA (Working) ; 109mA (Standby) ;200mA (Max)	System Supported	Linux, Android, MAC, Windows XP、7、8、10
Weight	108g±5g (Without cable)	Resolution	≥4mil
Size	L*W*H:180.1 * 88.7 * 66.3 (mm)	Reading Mode	Image
Color	Black / White	Reading Range	10mm-600mm



Prompt Mode	Buzzer, Indicator Light(LED)	Trigger Mode	Manual; Continuous scanning
IP Grade	IP42	Shock Resistance	Free fall 1.2m (concrete floor)
Language Supported	American; French; German; Hungary; Italian; Spanish; 【 Virtual Keyboard is supported 】		
Decoding Capability	1D: Code25-Interleaved Code25-Standard Code25-Matri RSS-14 Code39-Regular Code39-FullASCII Code93-Regular Code93-FullASCII Code128 EAN/JAN-13 UPCE0/E1 JAN/EAN-8 EAN/GSL/UCC-128Auto Codabar MSI UPC-A Code11 2D: Data Matrix PDF417 Micro QR HanXin QR Micro PDF 417 Maxi Code Aztec Scanning Depth		
Scanning Depth	QR 9.17 mil (7 byte) :6cm - 10cm Data Matrix 9.17mil (7 byte):7cm - 10cm Code93 5.83mil (14 byte) :7cm - 10cm		