

Wired 2D Barcode Scanner

POS760E

Application Industry

Store / Restaurant / Pharmacy / Ticket barrier



Specifications

Material	ABS+PC	Interface	USB (RS232 can be customized)
Power Supply	DC 5V \pm 5%	Sensor	Planar CMOS sensor 640*480
Operating Current	952mW (Working) ; 512mW (Standby) ;1105mW (Max)	System Supported	Linux, Android, MAC, Windows XP、7、8、10
Weight	121g \pm 5g (Without cable)	Resolution	5mil
Size	L*W*H:170 * 70 * 88 (mm)	Reading Mode	Image
Color	Grayish white;Black	Processor	32-bit ARM MCU + BGA



Prompt Mode	Buzzer, Indicator Light(LED)	Trigger Mode	Manual; Auto-Sensing		
IP Grade	IP54	Shock Resistance	Free fall 1.5m (concrete floor)		
Language Supported	US English ; Belgium ; Finland ; France ; Germany ; Italy ; Sweden ; United Kingdom ; Denmark ; Norway ; Spain ; Portugal ; Turkey F ; Turkey Q ; Japan ; etc. (Support International language)				
Decoding Capability	1D: Code25-Interleaved	Code25-Standard	Code25-Matri	Code32	Code128
	Code39-Regular	Code39-FullASCII	EAN/JAN-13	UPC-A	JAN-8
	Code93-Regular	Code93-FullASCII	Codabar	UPCE0	MSI
	EAN/GSL/UCC-128Auto	Code11			
	2D: Data Matrix	QR	PDF417	Maxicode	Aztec
					Hanxin
Scanning Depth	Code39 10mil:6cm - 25cm		QR 10mil:4cm - 25cm		